

Item #	
Project	
Date _	



## Model # D35 Triple Bowl Premix Dispensers Features

- Famous two-piece, stainless steel, dripless pouring valves are sanitary and easy to use and maintain.
- Better design and more stainless steel allow easier cleaning and less maintenance.
- Superior engineering allows full beverage cooling right down to the last drink.
- Large, 5 gallon bowls, with easy to read measuring marks, are separate to allow bowl cleaning and flavor changes without "total system shut-down".
- Super-strong, virtually unbreakable polycarbonate bowls and covers give lasting durability.
- Unique evaporator and high efficiency pump cools faster and more efficiently for faster start-ups.
- Choice of Regular (-4) or optional Stainless Steel (-3) side panels and drain trays.
- Down-to-earth design engineering makes routine servicing easier and simpler.
- Second-to-none quality with "field condition" testing.
- Optional whipper for frothed drinks.
- Agitators are included with each unit for fresh juices, coffees or teas.
- World-wide sales and service assure customer satisfaction.




GRINDMASTER<sup>®</sup>



Grindmaster® Coffee Grinders and Brewers • PrecisionBrew™ Brewing Systems • Espressimo® Espresso Machines Crathco® Hot Beverage Dispensers • Crathco® Cold and Frozen Beverage Dispensers • AMW Coffee and Tea Systems Tel (502) 425-4776 • Fax (502) 425-4664 • 1-800-695-4500 (USA & Canada only) P.O. Box 35020 • Louisville, KY 40232 • USA www.grindmaster.com • email: info@grindmaster.com

## **Crathco**<sub>®</sub> Model # D35 Triple Bowl

## **Premix Dispensers**



Specifications	<b>D35</b> (115V/60Hz)	D355 (230V/50Hz)	D356 (230V/60Hz)
# Bowls	3	3	3
Bowl Capacity	5 gallons (18.9L)	5 gallons (18.9L)	5 gallons (18.9L)
Refrigeration	1/3 hp	1/3 hp	1/3 hp
Volts / Hz / Amps	115V / 60Hz / 8.5Amp	230V / 50Hz / 4.3Amp / 989 Watts	230V / 60Hz / 4.3Amp / 989 Watts
Dimensions	27 1/4" x 25 5/8" x 15 7/8"	27 1/4" x 25 5/8" x 15 7/8"	27 1/4" x 25 5/8" x 15 7/8"
(H x W x D)	(69 cm x 65 cm x 40 cm)	(69 cm x 65 cm x 40 cm)	(69 cm x 65 cm x 40 cm)
Ship Weight (2 boxes)	95 lbs (base: 71, bowls: 24)	95 lbs (base: 71, bowls: 24)	95 lbs (base: 71, bowls: 24)
Ship Weight (2 boxes)	43 kg (base: 32.2, bowls: 10.8)	43 kg (base: 32.2, bowls: 10.8)	43 kg (base: 32.2, bowls: 10.8)
Cup Height	8-1/4" (21 cm)	8-1/4" (21 cm)	8-1/4" (21 cm)
Listings	UL, NSF, CUL	NSF, CE	NSF, CE

Specifications are subject to improvement or change without notice.

Standard Op									
		Stainless steel material (additional charge), -4 off-white high impact plastic (standard - no additional charge)							
Valve cap (part# 2039) Improve		proves sealing of valve when using pulpy products							
Valve locking box (part# 2502) (use w/ standard handle) Secures		ecures the valve from dispensing during off-hours - not to be used with non-contact handle							
Liquid Auto Fill (part# 90295) Ensures		usures proper product and mixing consistency, maintains optimum product level in bowls, eliminates need for frequent manual mixing							
Shipboard kit (part# 5925) Makes		akes unit safer for installation aboard marine vessel; only available for use with agitator							
Milk Fat Impellers Use wit		with milk-based products, and/or products with heavy pulp							
Condensation Control Direct a		irect and conceal condensation in high humidity or outdoor locations							
<b>Custom Optic</b>	<b>ons</b> * (available	with m	ninimum purchase quar	ntity)					
Frosted Bowls 5 g			rosted surface simulates condensation while helping hide product residue and offering added UV protection.						
Frosted Lid	Frosted Lid Lid with		id with frosted surface for use with 5 gallon (18.9L) frosted bowls						
Whippers (must be ordered when ordering machine) (see models in spec chart below)		Great fo	Great for iced cappuccinos and iced coffee. Whips beverage upon dispensing to create a frothy top on drink.						
	1WD35 (115V/6		2WD35 (115V/60Hz)	3WD35 (115V/60Hz)		2WD355 (230V/50Hz)	3WD355 (230V/50Hz)		
Whipper Models	(3 bowls - 1 whip	per)	(3 bowls - 2 whippers)	(3 bowls - 3 whippers)	(3 bowls - 1 whipper)	(3 bowls - 2 whippers)	(3 bowls - 3 whippers)		
Bowl Capacity	5 gallons (18.9L)		5 gallons (18.9L)	5 gallons (18.9L)	5 gallons (18.9L)	5 gallons (18.9L)	5 gallons (18.9L)		
Refrigeration	1/3 hp		1/3 hp	1/3 hp	1/3 hp	1/3 hp	1/3 hp		
Volts / Hz / Amps	115V / 60Hz / 9.1	l Amp	115V / 60Hz / 9.7Amp	115V / 60Hz / 10.3Amp	230V / 50Hz / 4.6Amp	230V / 50Hz / 4.9Amp	230V / 50Hz / 5.2Amp		
Dimensions (H x W x D)	29 3/4" x 25 5/8" x (76cm x 65cm x 4			29 3/4" x 25 5/8" x 15 7/8" (76cm x 65cm x 40cm)	29 3/4" x 25 5/8" x 15 7/8" (76cm x 65cm x 40cm)	29 3/4" x 25 5/8" x 15 7/8" (76cm x 65cm x 40cm)	29 3/4" x 25 5/8" x 15 7/8" (76cm x 65cm x 40cm)		
Ship Weight (2 boxes)	97 lbs (74 lbs, 23 44 kg (33.5 kg, 1	,	98 lbs (76 lbs, 22 lbs) 44.5 kg (34.5 kg, 10 kg)	100 lbs (78 lbs, 22 lbs) 45.4 kg (35.4 kg, 10 kg)	97 lbs (74 lbs, 23 lbs) 44 kg (33.5 kg, 10.5 kg)	98 lbs (76 lbs, 22 lbs) 44.5 kg (34.5 kg, 10 kg)	100 lbs (78 lbs, 22 lbs) 45.4 kg (35.4 kg, 10 kg)		
Cup Height	5-1/2" (14 cm)		5-1/2" (14 cm)	5-1/2" (14 cm)	5-1/2" (14 cm)	5-1/2" (14 cm)	5-1/2" (14 cm)		
Listings	UL, NSF, CUL		UL, NSF, CUL	NSF, UL, CUL	NSF, CE	NSF, CE	NSF, CE		

\* Additional cost applies

US





Specifications are subject to improvement or change without notice.

Tel (502) 425-4776 • Fax (502) 425-4664 • 1-800-695-4500 (USA & Canada only) P.O. Box 35020 • Louisville, KY 40232 • USA

© Grindmaster Corporation, 2002 Printed in USA

www.grindmaster.com • email: info@grindmaster.com

